

Teste a snodo SI SI40-ES-2RS-DURBAL - SI40-ES-2RS-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/si40-es-2rs-durbal>

SI40-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.


Rod end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and
phosphated

Outer ring:
bearing steel, hardened, ground and
phosphated

Lubrication:
lubrication required



order number		measurement [mm]						
right hand thread	left hand thread	d	G	B	C1	d2	d3	d4
SI 40 ES (-2RS)		40	M 39 x 3	28	23,0	92	52,0	65
type	l ₂ min	measurement [mm]		h	α [°]	load rating C ₀ [kN]	weight [kg]	
SI / SII 40 ES (-2RS)	65	W		142	7	180,0	2,0	

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952497389
Diametro interno	40 mm
Diametro esterno	92 mm
Spessore	28 mm
Tipo	SI
Peso	2000 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE