

## Teste a snodo SI SI45-ES-2RS-DURBAL - SI45-ES-2RS-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/si45-es-2rs-durbal>

### SI45-ES-2RS



female thread;  
lubrication  
required,  
according to  
DIN ISO 12240-4;  
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter  $d \geq 15$  with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter  $d \geq 15$  type DSI...ES-2RS with additional seals also available.


Rod end body:  
surface zinc plated

Sliding combination:  
steel / steel

Inner ring:  
bearing steel, hardened, ground and  
phosphated

Outer ring:  
bearing steel, hardened, ground and  
phosphated

Lubrication:  
lubrication required



order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C1	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>
SI 45 ES (-2RS)		45	M 42 x 3	32	27,0	102	58,0	70

type	measurement [mm]			$\alpha$ [°]	load rating C <sub>0</sub> [kN]	weight [kg]
	l <sub>3</sub> min	W	h			
SI / SII 45 ES (-2RS)	65	60	145	7	240,0	2,5

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952497518
Diametro interno	45 mm
Diametro esterno	102 mm
Spessore	32 mm
Tipo	SI
Peso	2500 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE