

Teste a snodo SI
SI80-ES-2RS-DURBAL - SI80-ES-2RS-DURBAL
<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/si80-es-2rs-durbal>


SI80-ES-2RS



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E



Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2RS with additional seals also available.



Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number		measurement (mm)						
right hand thread	left hand thread	d	G	B	C ₁	d ₂	d ₃	d ₄
SI 80 ES (-2RS)		80	M 64 x 4	55	47,0	180	95,0	110

type	measurement (mm)			α [°]	load rating C ₀ [kN]	weight [kg]
	l ₂ min	W	h			
SI / S1L 80 ES (-2RS)	85	100	230	6	750,0	12,0

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952497785
Diametro interno	80 mm
Diametro esterno	180 mm
Spessore	55 mm
Tipo	SI
Peso	12000 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE