

Teste a snodo SI SIL80-ES-DURBAL - SIL80-ES-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/sil80-es-durbal>

SIL80-ES



female thread;
lubrication
required,
according to
DIN ISO 12240-4;
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSI...ES-2/R5 with additional seals also available.

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number

right hand thread	left hand thread	measurement (mm)						
		d	G	B	C ₁	d ₂	d ₃	d ₄
SIL 80 ES		80	M 64 x 4	55	47,0	180	95,0	110

measurement [mm]

type	l ₃ min	W	h	α [°]	load rating C ₀ [kN]	weight [kg]
SI / SIL 80 ES	85	100	230	6	750,0	12,0

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952497822
Diametro interno	80 mm
Diametro esterno	180 mm
Spessore	55 mm
Tipo	SI
Peso	12000 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE