

Teste a snodo SA SAL15-ES-2RS-DURBAL - SAL15-ES-2RS-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/sal15-es-2rs-durbal>

SAL15-ES-2RS



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]					
right hand thread	left hand thread	d	G	B	C ₁	d ₂	
	SAL 15 ES (-2RS)	15	M 14	12	10,0	40	
type	l ₁ min	l ₂	h	n [°]	load rating C ₀ [kN]	weight [kg]	
SA / SAL 15 ES (-2RS)	34	20	63	8	36,0	0,140	

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952498065
Diametro interno	15 mm
Diametro esterno	40 mm
Spessore	12 mm
Tipo	SA
Peso	140 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	-
Standard	Nessuno standard

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE