

Teste a snodo SA SAL20-ES-DURBAL - DSAL20-ES-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/dsal20-es-durbal>

SAL20-ES



male thread:
lubrication
is necessary,
according to
DIN ISO 12240-4,
series E

Description: DIN ISO rod end E series. Made of spherical plain bearing DGE...E (ES) pressed into rod end body. Sliding combination steel / steel. Maintenance necessary. Bore diameter $d \geq 15$ with grease nipple in rod end body and lubrication groove and hole in inner and outer ring. Bore diameter $d \geq 15$ type DSA...ES-2RS with additional seals also available.


Ball end body:
surface zinc plated

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication is necessary



order number		measurement [mm]				
right hand thread	left hand thread	d	G	B	C ₁	d ₂
	SAL 20 ES	20	M 20 x 1,5	16	13,0	53

type	measurement [mm]			n [°]	load rating C ₀ [kN]	weight [kg]
	l ₁ min	l ₂	h			
SA / SAL 20 ES	43	27	78	9	60,0	0,310

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952498232
Diametro interno	20 mm
Diametro esterno	53 mm
Spessore	16 mm
Tipo	SA
Peso	310 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE