

Teste a snodo TAPR GIHO-K-12DO-DURBAL - GIHO-K-12DO-DURBAL

https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/tapr/giho-k-12do-durbal

GIHO-K-12DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number		measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₄	d ₅	B	C ₁	C ₂	
GIHO-K 12 DO*		12	15,0	35	M 10 x 1,25	17	40	10	8	13	

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 12 DO*	42	15	59,5	16	11	17,0	0,12

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952500607
Diametro interno	12 mm
Diametro esterno	35 mm
Spessore	8 mm
Tipo	TAPR
Peso	120 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE