

Teste a snodo TAPR

GIHO-K-16DO-DURBAL - GIHO-K-16DO-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/tapr/giho-k-16do-durbal>

GIHO-K-16DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

Female thread: hydraulic rod ends, according to DIN 24555

Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple

order number	measurement [mm]		
right hand thread	left hand thread		
GIHO-K 16 DO*	16	20,7 45	M 12 x 1,25 21 45 14 11 13

type	measurement [mm]				α [°]	load rating C_0 [kN]	weight [kg]
	h_1	l_1	l_2	l_3			
GIHO-K / GIHO-KL 16 DO	48	17	70,5	20	10	28,5	0,22

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952500652
Diametro interno	16 mm
Diametro esterno	45 mm
Spessore	11 mm
Tipo	TAPR
Peso	220 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE