

Teste a snodo TAPR GIHO-KL-20DO-DURBAL - GIHO-KL-20DO-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/tapr/giho-kl-20do-durbal>

GIHO-KL-20DO



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

female thread: hydraulic rod ends, according to DIN 24555


Sliding combination: steel / steel

Inner ring: bearing steel, hardened, ground and phosphated

Outer ring: bearing steel, hardened, ground and phosphated

Lubrication: lubrication required

* without grease nipple



order number	measurement [mm]	
right hand thread	left hand thread	
GIHO-KL 20 DO*		
	d	d ₁ d ₂
	20	24,1 55
	G	M 14 x 1,5
	d ₃	25
	B	55
	C ₁	16
	C ₂	13
	C ₃	17

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 20 DO	58	19	85,5	25	9	42,5	0,43

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952500690
Diametro interno	20 mm
Diametro esterno	55 mm
Spessore	13 mm
Tipo	TAPR
Peso	430 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE