


Teste a snodo TAPR

GIHO-K-25DO-DURBAL - GIHO-K-25DO-DURBAL


<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/tapr/giho-k-25do-durbal>


GIHO-K-25DO

Female thread:
hydraulic rod ends,
according to
DIN 24555



Description: Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE- ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.





* without grease nipple

Sliding combination:
steel / steel

Inner ring:
bearing steel, hardened, ground and phosphated

Outer ring:
bearing steel, hardened, ground and phosphated

Lubrication:
lubrication required

order number		measurement [mm]									
right hand thread	left hand thread	d	d ₁	d ₂	G	d ₃	d ₄	B	C ₁	C ₂	
GIHO-K 25 DO		25	29,3	65	M 16 x 1,5	30	62	20	17	17	

type	measurement [mm]				α [°]	load rating C ₀ [kN]	weight [kg]
	h ₁	l ₁	l ₂	l ₃			
GIHO-K / GIHO-KL 25 DO	68	23	100,5	30	7	67,0	0,67

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952500737
Diametro interno	25 mm
Diametro interno	0.984" inch
Diametro esterno	65 mm
Diametro esterno	2.559" inch
Spessore	17 mm
Spessore	0.669" inch
Tipo	TAPR
Peso	670 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE