

## Teste a snodo TAPR GIHO-KL-40DO-DURBAL - GIHO-KL-40DO-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/tapr/giho-kl-40do-durbal>

### GIHO-KL-40DO



**Description:** Hydraulic rod end with slot and clamping arrangement. Made of spherical plain bearing DGE. ES pressed into rod end housing. Sliding combination steel/steel with grease nipple.

**Female thread:** hydraulic rod ends, according to DIN 24555


**Sliding combination:** steel / steel

**Inner ring:** bearing steel, hardened, ground and phosphated

**Outer ring:** bearing steel, hardened, ground and phosphated

**Lubrication:** lubrication required

\* without grease nipple



order number	measurement [mm]	
right hand thread	left hand thread	
GIHO-KL 40 DO		
	d	d <sub>1</sub> d <sub>2</sub>
	40	45,0 100
	M	27 x 2
	G	d <sub>3</sub> d <sub>4</sub>
	45	90 28
	B	C <sub>1</sub> C <sub>2</sub>
	23	23 23

type	measurement [mm]			α [°]	load rating C <sub>0</sub> [kN]	weight [kg]	
	h <sub>1</sub>	l <sub>1</sub>	l <sub>2</sub>				
GIHN-K / GIHN-KL 40 DO	105	37	155,0	45	7	156,0	2,16

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952500805
Diametro interno	40 mm
Diametro esterno	100 mm
Spessore	23 mm
Tipo	TAPR
Peso	2160 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE