

Snodi sferici GE

BRTM12-01-502-DURBAL - BRTM12-01-502-DURBAL


<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/brtm12-01-502-durbal>

BRTM12-01-502



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**



rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

liner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number			measurements [mm]						
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	b ₁	b ₂	b ₃
BRTM 12 -01	-502		12	M 12		14,5	32	16	12
measurements [mm]			weight		rotational speed limit		basic load rating		stat.
type	h	l	b ₃	α	[kg]	n _{max} [min ⁻¹]	C	d _m	C ₀
BRTM 12	54	33	19	7,5	0,088	1125	10250		6600

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3616060468161
Diametro interno	12 mm
Diametro esterno	32 mm
Spessore	16 mm
Tipo	GE
Peso	88 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE