

## Teste a snodo SA BRTM25-00-502-DURBAL - BRTM25-00-502-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/brtm25-00-502-durbal>

### BRTM25-00-502



male thread:  
long-term  
lubrication,  
low maintenance,  
shields,  
adapter sizes  
according to  
DIN ISO 12240-4,  
series K

**DURBAL® heavy-duty rod ends  
with integral self-aligning  
roller bearing**

rod end housing:  
forged steel, case-hardened bearing race,  
superfinished, rolled thread, surface gal-  
vanized, free of Cr-VI


liner ring:  
ball bearing steel, hardened,  
superfinished

lubrication:  
aluminum-complex soap grease,  
temperature range: -45 °C to +120 °C,  
approval according to USDA H1

lubrication fitting:  
DIN 71 412 H1

bearing clearance:  
10 - 30 µm radial

tolerances:  
see page 10



order number		measurements [mm]									
type	type hard thread	left hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>6</sub>	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>	
BRTM 25 -00	-502		25	M 24 x 2	29,5	64	31	22			
measurements [mm]		weight	rotational speed limit	basic load rating	dyn.	stat.					
type	h	l	b <sub>3</sub>	α [°]	[kg]	n <sub>max</sub> [rpm]	C [N]	C <sub>0</sub> [N]			
BRTM 25	94	57	30	5,0	0,596	600	24900	18500			

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952506784
Diametro interno	25 mm
Diametro interno	0.984" inch
Diametro esterno	64 mm
Diametro esterno	2.52" inch
Spessore	31 mm
Spessore	1.22" inch
Tipo	SA
Peso	596 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE