

Snodi sferici GE

BRTM30-00-501-DURBAL - BRTM30-00-501-DURBAL


<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/brtm30-00-501-durbal>

BRTM30-00-501



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K

**DURBAL® heavy-duty rod ends
with integral self-aligning
roller bearing**



rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI

liner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range: -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number			measurements [mm]								
type	size	thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	b ₁	b ₂	b ₃
BRTM 30 -00	-501	M 30 x 2	30			34,5		70		37	25

measurements [mm]					weight [kg]	rotational speed limit n _{max} [rpm]	basic load rating	
type	h	l	b ₃	α [°]			C [N]	C ₀ [N]
BRTM 30	110	66	35	7,5	0,912	450	32500	24850

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3616060468178
Diametro interno	30 mm
Diametro interno	1.181" inch
Diametro esterno	70 mm
Diametro esterno	2.756" inch
Spessore	37 mm
Spessore	1.457" inch
Tipo	GE
Peso	912 g
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE