

Snodi sferici GE

BRTF20-00-501-DURBAL - BRTF20-00-501-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/brtf20-00-501-durbal>

BRTF20-00-501



rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished


lubrication:
aluminium complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 71 412 H1


bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning roller bearing



female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K



order number			measurements [mm]									
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	h ₁	h ₂	
BRTF 20 -00	-501		20	27,5	M 20 x 1,5	24,5	50	34	25	18		
			measurements [mm]				weight	rotational speed limit	basic load rating			
type	h	l	l ₁	l ₂	SW	α [°]	[kg]	n _{max} [min ⁻¹]	C [N]	stat. C ₀ [N]		
BRTF 20	77	33	10,0	26	30	7,0	0,361	825	17000	11700		

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3616060468185
Diametro interno	20 mm
Diametro esterno	50 mm
Spessore	25 mm
Tipo	GE
Peso	361 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE