

## Teste a snodo SI BRF25-00-502-DURBAL - BRF25-00-502-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/brf25-00-502-durbal>

### BRF25-00-502



**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI.

**inner ring:**  
ball bearing steel, hardened, superfinished.

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1



**lubrication fitting:**  
DIN 3405 D1/A (sizes 6 to 10)  
DIN 71 412 H1 (sizes 12 to 30)

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**female thread:**  
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K

order number		measurements [mm]										
type	right-hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>7</sub>	b <sub>1</sub>	b <sub>2</sub>	h		
BRF 25 -00	-502	25	30,0	M 24 x 2	29,5	64	35	31	22,0	94		
measurements [mm]		weight	calculation-factors	rotational speed limit	basic load rating							
type	l	l <sub>1</sub>	l <sub>2</sub>	SW	α [°]	β [°]	Y	Y <sub>0</sub>	n <sub>max</sub> [min <sup>-1</sup> ]	C [N]	C <sub>0</sub> [N]	
BRF 25	42	10,0	32	30	5,0	0,572	2,02	2,12	600	11030	5680	

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507323
Diametro interno	25 mm
Diametro esterno	64 mm
Spessore	31 mm
Tipo	SI
Peso	572 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE