

Teste a snodo SI PF20-00-502-DURBAL - PF20-00-502-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/pf20-00-502-durbal>

PF20-00-502



rod end housing:
forged steel, case-hardened bearing race,
superfined, surface galvanized,
free of Cr VI

inner ring:
ball bearing steel, hardened,
superfined


lubrication:
aluminium-complex soap-grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 3485 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**



female thread;
long-term
lubrication,
low maintenance,
shields



order number		measurements [mm]										
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	b ₁	b ₂	b ₃	
PF 20 -00		-502	20	22	M 16	24,0	48	20,5	15			
measurements [mm]		weight	calculation factors	rotational speed limit	basic load rating							
type	h	l	r	SW	α	γ	Y	Y ₀	lim [min]	C	C ₀	
PF 20	65	32	22,0	20	19	6,5	0,223	2,34	2,45	850	6105	2955

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507415
Diametro interno	20 mm
Diametro esterno	48 mm
Spessore	20.5 mm
Tipo	SI
Peso	223 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE