

Teste a snodo SA

PM05-00-501-DURBAL - PM05-00-501-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/pm05-00-501-durbal>

PM05-00-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating	
type	type	d1	d2	d4	d7	b1	b2	Y	Yc	C	C0
PM 05 -00	-501	5	M 8 x 1	7,5	19	12	12	1350	1610	480	
type	l1	l2	l3	h1	h2	u	z	alpha	alpha prime		
PM 05	39,5	13	57	1,5	2,5	7,0	0,037	1,51	1,58		

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507422
Diametro interno	5 mm
Diametro esterno	19 mm
Spessore	12 mm
Tipo	SA
Peso	37 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE