

## Teste a snodo SA

### PM05-01-502-DURBAL - PM05-01-502-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/pm05-01-502-durbal>

#### PM05-01-502



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10



order number		measurements [mm]					measurements [mm]					weight			rotational speed limit			basic load rating	
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	Y	Yc	nmax [min-1]	C [N]	C0 [N]	dyn.	stat.	C0 [N]	C0 [N]
PM 05 -01	-502	5	M 8 x 1	7,5	19	12	12	12	8										
type		l1	l2	l3	h1	h2	u	z	alpha	alpha prime									
PM 05	16	13	33,5	1,5	2,5	7,0	0,033	1,51	1,58			1350	1610	480					

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507446
Diametro interno	5 mm
Diametro esterno	19 mm
Spessore	12 mm
Tipo	SA
Peso	33 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE