

## Teste a snodo SA

### PM08-02-502-DURBAL - PM08-02-502-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/pm08-02-502-durbal>

#### PM08-02-502



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10



order number		measurements [mm]			weight			rotational speed limit			basic load rating			
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	C	C0		
PM 08-02	-502	8	M 12 x 1.5	11,0	30	17	15	10						
measurements [mm]		weight		rotational speed limit		basic load rating								
type	l1	l2	l3	h1	h2	u	z	alpha	alpha prime	Y	gamma	nmax [min-1]	dyn. [N]	stat. [N]
PM 08 23	20	48,5	2,0	2,5	8,5	0,088	1,9	1,81	1225	2605	985			

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507521
Diametro interno	8 mm
Diametro esterno	30 mm
Spessore	15 mm
Tipo	SA
Peso	88 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE