

## Teste a snodo SA

### PM10-03-501-DURBAL - PM10-03-501-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/pm10-03-501-durbal>

#### PM10-03-501



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/AH1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10



order number		measurements [mm]		measurements [mm]		weight		rotational speed limit		basic load rating		
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	l1	
PM 10 -03	-501	10	M 14 x 1,5	12,5	36	19	20	14				
measurements [mm]		weight		rotational speed limit		basic load rating						
type	l1	l2	l3	h1	h2	u	z	alpha	alpha prime	Y	Yc	
PM 10	26	28	58,5	2,5	2,5	9,5	0,154	1,69	1,77	1100	5120	1905

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507576
Diametro interno	10 mm
Diametro esterno	36 mm
Spessore	20 mm
Tipo	SA
Peso	154 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE