

Teste a snodo SA

PM15-00-501-DURBAL - PM15-00-501-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/pm15-00-501-durbal>

PM15-00-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]		weight		rotational speed limit		basic load rating	
type	type	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂
PM 15 -00	-501	15	M 20 x 1,5	18,5	42	26	20	14	
measurements [mm]		weight		rotational speed limit		basic load rating			
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α	α'
PM 15	62,5	30	100	3,0	2,5	6,5	0,310	2,07	2,17
		weight		rotational speed limit		basic load rating			
type	Y	Y _c	n _{max} [min ⁻¹]	C	C ₀	[N]	C ₀	[N]	
PM 15			975	5485	3270				

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507620
Diametro interno	15 mm
Diametro esterno	42 mm
Spessore	20 mm
Tipo	SA
Peso	310 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE