

PM15-00-502-DURBAL - PM15-00-502-DURBAL

PM15-00-502



**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr VI

inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex-soap-grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:

tolerances:

type	order number specification						measurements [mm]						
	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	b ₁	b ₂	b ₃			
PM 15-00	-502	15	M 20 x 1,5	18,5	42	26	20	14					
measurements [mm]						weight	calculation-factors	rotational speed limit	basic load rating	dyn. stat.			
t ₁	t ₂	t ₃	b ₁	b ₂	z	α [°]	y ₀	n _{lim} [min ⁻¹]	C [N]	N ₁	N ₂	N ₃	N ₄
PM 15	62,5	30	100	30	2,5	6,5	0,310	2.07 · 10 ⁴	975	5085	3270		

Marchio	DURBAL
N° Ean13	3663952507637
Diametro interno	15 mm
Diametro esterno	42 mm
Spessore	20 mm
Tipo	SA
Peso	310 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

+33 3 59 36 04 90

01/12/2024