

Teste a snodo SA

PM15-02-501-DURBAL - PM15-02-501-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/pm15-02-501-durbal>

PM15-02-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to ISO/AH1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]			measurements [mm]			measurements [mm]			measurements [mm]			
type	type	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃	weight	calculation factors	rotational speed limit	basic load rating
PM 15 -02 -501		15	M 20 x 1.5	18.5	42	26	20	14						
measurements [mm]		measurements [mm]			measurements [mm]			measurements [mm]			measurements [mm]			
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α	α'	weight [kg]	Y	Y _c	n _{max} [min ⁻¹]	C [N]
PM 15	36	30	73.5	3.0	2.5	6.5	0.273				2.07	2.17	975	5485 3270

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507651
Diametro interno	15 mm
Diametro esterno	42 mm
Spessore	20 mm
Tipo	SA
Peso	273 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE