

Teste a snodo SA

PM17-00-502-DURBAL - PM17-00-502-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/pm17-00-502-durbal>

PM17-00-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]			measurements [mm]			measurements [mm]					
type	sp/roct/mad	id/bad/rim	d ₁	d ₂	d ₄	d ₅	d ₇	b ₁	b ₂	b ₃			
PM 17 -00	-502	17	M 20 x 1,5	21,0	48	25	22	16					
type		measurements [mm]			weight	calculation factors		rotational speed limit		basic load rating			
l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α [°]	α' [°]	Y	Y _c	n _{max} [min ⁻¹]	C [N]	C ₀ [N]
PM 17	62,5	36	105	3,5	2,5	7,0	0,401		2,35	2,46	875	5575	2680

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507675
Diametro interno	17 mm
Diametro esterno	48 mm
Spessore	22 mm
Tipo	SA
Peso	401 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE