

**Teste a snodo SA**  
**PM17-01-502-DURBAL - PM17-01-502-DURBAL**  
<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/pm17-01-502-durbal>

**PM17-01-502**



**male thread:**  
long-term lubrication, low maintenance, shields

**DURBAL® heavy-duty rod ends with integral self-aligning ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI

**inner ring:**  
ball bearing steel, hardened, superfinished

**lubrication:**  
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

**lubrication fitting:**  
DIN 3405 D1/A

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10

order number		measurements [mm]			measurements [mm]			measurements [mm]				
type	type	type	type	type	type	type	type	type	type	type		
PM 17 -01	-502	17	M 20 x 1,5	21,0	48	25	22	16				
measurements [mm]		weight	calculation factors	rotational speed limit	basic load rating							
type	type	type	type	type	type	type	type	type				
PM 17	36	36	78,5	3,5	2,5	7,0	0,354	2,35	2,46	875	5575	2680

**CARATTERISTICHE DEL PRODOTTO**

Marchio	DURBAL
N° Ean13	3663952507682
Diametro interno	17 mm
Diametro esterno	48 mm
Spessore	22 mm
Tipo	SA
Peso	354 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE