

Teste a snodo SA

PM17-01-502-DURBAL - PM17-01-502-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/pm17-01-502-durbal>

PM17-01-502



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]			measurements [mm]			measurements [mm]								
type	type	type	type	type	type	type	type	type	type	type						
PM 17 -01	-502	17	M 20 x 1,5	21,0	48	25	22	16								
measurements [mm]		weight	calculation factors	rotational speed limit	basic load rating		stat.									
type	l ₁	l ₂	l ₃	h ₁	h ₂	u	z	α	α'	Y	Y _c	n _{max} [min ⁻¹]	C [N]	C ₀ [N]	C ₀ [N]	
PM 17	36	36	78,5	3,5	2,5	7,0						2,35	2,46	875	5575	2680

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507682
Diametro interno	17 mm
Diametro esterno	48 mm
Spessore	22 mm
Tipo	SA
Peso	354 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE