

Teste a snodo SA

PM20-02-501-DURBAL - PM20-02-501-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/pm20-02-501-durbal>

PM20-02-501



male thread:
long-term lubrication, low maintenance, shields

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing

rod end housing:
forged steel, case-hardened bearing race, superfinished, rolled thread, surface galvanized, free of Cr-VI


inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminium-complex-soap-grease, temperature range -45 °C to +120 °C, approval according to ISO/A H1

lubrication fitting:
DIN 3405 D1/A

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [mm]		weight		calculation factors		rotational speed limit		basic load rating	
type	type	d1	d2	d3	d4	d5	d7	b1	b2	b3	
PM 20 -02	-501	20	M 24 x 1,5	24,0	56	30	24	18			
measurements [mm]		weight		calculation factors		rotational speed limit		basic load rating			
type	l1	l2	l3	h1	h2	u	z	alpha	alpha prime	Y	Yc
PM 20	41	41	89,5	3,5	3,0	5,5				2,76	2,90
										775	6165
											3140

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952507736
Diametro interno	20 mm
Diametro esterno	56 mm
Spessore	24 mm
Tipo	SA
Peso	519 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE