

Teste a snodo SA
BRM08-60-502-DURBAL - BRM08-60-502-DURBAL
<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/brm08-60-502-durbal>


BRM08-60-502



male thread:
long-term
lubrication,
low maintenance,
shields,
adapter sizes
according to
DIN ISO 12240-4,
series K



**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing in stainless steel**



rod end housing:
stainless steel 1.4034, hardened; bearing
race superfinished, rolled thread

inner ring:
stainless steel, hardened,
surface superfinished

lubrication:
aluminium-complex soap-grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 3402 D1/L6 (sizes 6 to 10)
DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

order number		measurements [mm]								
type	right-hand thread	d1	d2	d3	d4	d5	l1	l2	l3	h
BRM 08 -60	-502	8	M 8		10,5	24	12	9,0		42
measurements [mm]		weight		calculation factors		rotational speed limit		basic load rating		
type	l	l2	α [°]	[kg]	Y	Y0	rpm	C	C0	stat. stat.
BRM 08	25	15	8,5	0,036	1,80	1,89	1300	2800		700

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952509105
Diametro interno	8 mm
Diametro esterno	24 mm
Spessore	12 mm
Tipo	SA
Peso	36 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE