

Teste a snodo SI BRF08-60-502-DURBAL - BRF08-60-502-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/brf08-60-502-durbal>

BRF08-60-502



DURBAL® heavy-duty rod ends with integral self-aligning ball bearing in stainless steel

rod end housing:
stainless steel 1.4034, hardened, bearing race superfinished

inner ring:
stainless steel, hardened, surface superfinished


lubrication:
aluminum-complex-soap-grease, temperature range: -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 D1/A (sizes 6 to 10), DIN 71 412 H1 (sizes 12 to 20)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

female thread:
long-term lubrication, low maintenance, shields, adapter sizes according to DIN ISO 12240-4, series K



order number		measurements [mm]												
type	light load thread	light load thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₇	b ₁	b ₂	h			
BRF 08-60	-502		8	12,5	M 8	10,5	24	16	12	9,0	36			
measurements [mm]		weight		calculation-factors		rotational speed limit		basic load rating		stat.				
type	l ₁	l ₂	l ₃	SW	α [°]	Y	λ	n _{max} [min ⁻¹]	C [N]	C ₁₀ [N]	C ₅₀ [N]			
BRF 08	16	5,0	12	14	8,5	0,044	1,80	1,89	1300	2800	700			

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952509228
Diametro interno	8 mm
Diametro esterno	24 mm
Spessore	12 mm
Tipo	SI
Peso	44 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE