

Teste a snodo SI BEF22-60-501-DURBAL - BEF22-60-501-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/bef22-60-501-durbal>

BEF22-60-501



rod end heading:
stainless steel 1.4301, rolled thread,
surface with pickling treatment


joint ball:
stainless steel, hardened and ground,
surface superfinished

race:
nylon / teflon / glass fibre compound

tolerances:
see page 10

**DURBAL® heavy-duty rod ends
with integral spherical
plain bearing in stainless steel**

female thread:
maintenance free,
adapter sizes
according to
DIN ISO 12240-4,
series K,
thread according to
ISO 8139



order number		measurements [mm]											
type	right hand thread	left hand thread	d ₁	d ₂	d ₃	d ₄	d ₅	d ₆	d ₇	d ₈	b ₁	b ₂	b ₃
BEF 22	-60	-501	22	30,0	M 22 x 1,5	54	38	38,05	28	20,0			
measurements [mm]		weight							basic load rating				
type	h	l	l ₁	l ₂	l ₃	SW	α ₁ [°]	α ₂ [°]	β [°]	C [N]	C ₀ [N]	stat.	
BEF 22	84	37	12,0	26	32	15,5	10,0		0,520	23480	63600		

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952509594
Diametro interno	22 mm
Diametro esterno	54 mm
Spessore	28 mm
Tipo	SI
Peso	520 g
Il filo	Filetto destro
Lubrificazione	senza
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE