


## Snodi sferici GE

### BRTM5-8-00-501-DURBAL - BRTM5-8-00-501-DURBAL


<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/ge/brtm5-8-00-501-durbal>

#### BRTM5/8-00-501



male thread:  
long-term  
lubrication,  
low maintenance,  
shields,  
dimensions in inches

**DURBAL® heavy-duty rod ends  
with integral self-aligning  
roller bearing**



rod end housing:  
forged steel, case-hardened bearing race,  
superfinished, rolled thread, surface gal-  
vanized, free of Cr-VI

inner ring:  
ball bearing steel, hardened,  
superfinished

lubrication:  
aluminum-complex soap grease,  
temperature range -45 °C to +120 °C,  
approval according to USDA H1

lubrication fitting:  
DIN 71 412 H1

bearing clearance:  
10 - 30 µm radial

tolerances:  
see page 10

order number		measurements [inches]								
type	right hand thread left hand thread	d <sub>1</sub>	d <sub>2</sub> class 2	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	d <sub>6</sub>	b <sub>1</sub>	b <sub>2</sub>	b <sub>3</sub>
BRTM 5/8 -00	-501	.625	.6250-18 UNF	.748	1.653	.826	.590			
		measurements [inches]			weight	rotational speed limit rpm [min <sup>-1</sup> ]	basic load rating dyn. C [N]	stat. C <sub>0</sub> [N]		
type		h	l	l <sub>2</sub>	α [°]	[kg]				
BRTM 5/8		2.618	1.574	.944	7,0	0,182	975	13300	8900	

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3616060468314
Diametro interno	15.88 mm
Diametro esterno	41.99 mm
Spessore	20.98 mm
Tipo	GE
Peso	182 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1
Standard	Nessuno standard

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE