

Teste a snodo SI BRTF1-1-01-501-DURBAL - BRTF1-1-01-501-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/brtf1-1-01-501-durbal>

BRTF1/1-01-501



red end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr VI

inner ring:
ball bearing steel, hardened, superfinished

lubrication:
aluminum-complex soap grease, temperature range -45 °C to +120 °C, approval according to USDA H1



lubrication fitting:
DIN 71 412 H1

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning roller bearing

female thread:
long-term lubrication, low maintenance, shields, dimensions in inches

order number		measurements [inches]									
type	right hand thread	left hand thread	d ₁	d ₂	d ₃ class 2	d ₄	d ₆	d ₇	b ₁	b ₃	
BRTF	1/1	-01	-501	1.000	1.171	1.0000-14 UNS	1.161	2.519	1.377	1.220	.866
measurements [inches]		weight	rotational speed limit	basic load rating							
type	h	l	l ₁	l ₃	SW	α [°]	max [mm]	C [N]	stat. C ₀ [N]	stat. C ₁₀ [N]	
BRTF	1/1	3.720	1.653	.236	1.279	1.181	5,0	0,568	600	24900	18500

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952510088
Diametro interno	25.4 mm
Diametro esterno	63.98 mm
Spessore	30.99 mm
Tipo	-
Peso	568 g
Il filo	-
Lubrificazione	-
Imballaggio	-

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE