

Teste a snodo SI
BRF1-1-00-502-DURBAL - BRF1-1-00-502-DURBAL
<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/brf1-1-00-502-durbal>

BRF1/1-00-502

rod end housing:
forged steel, case-hardened bearing race, superfinished, surface galvanized, free of Cr-VI

inner ring:
ball bearing steel, hardened, superfinished


lubrication:
aluminum complex soap-grease, temperature range -45 °C to +120 °C, approval according to USDA H1

lubrication fitting:
DIN 3405 DT1A (sizes 1/4 and 3/8)
DIN 71 412 H1 (sizes 1/2 and 1/1)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10

DURBAL® heavy-duty rod ends with integral self-aligning ball bearing



female thread:
long-term lubrication, low maintenance, shields, dimensions in inches



order number		measurements [inches]									
type	right hand thread left hand thread	d1	d2	d3 class 2	d4	d5	d6	d7	b1	b2	
BRF 1/1 -00	-502	1.000	1.171	1.0000-12 UNF	1.161	2.519	1.377	1.220	.866		
measurements [inches]		weight		calculation factors	rotational speed limit	basic load rating					
type	h	l	l1	l2	SW	α [°]	Y	Yc	rpm	C [N]	C0 [N]
BRF 1/1	3.720	1.653	.236	1.279	1.181	5.0	0.570	2.02 2.12	600	11030	5680

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952510200
Diametro interno	25.4 mm
Diametro esterno	63.98 mm
Spessore	30.99 mm
Tipo	SI
Peso	570 g
Il filo	Filetto sinistro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it
+33 3 59 36 04 90
CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE