

## Teste a snodo SA BRM1-2-00-501-DURBAL - BRM1-2-00-501-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/brm1-2-00-501-durbal>

### BRM1/2-00-501



**male thread:**  
long-term  
lubrication,  
low maintenance,  
shields,  
dimensions in inches

**DURBAL® heavy-duty rod ends  
with integral self-aligning  
ball bearing**

**rod end housing:**  
forged steel, case-hardened bearing race,  
superfinished, rolled thread, surface gal-  
vanized, free of Cr-VI


**inner ring:**  
ball bearing steel, hardened,  
superfinished

**lubrication:**  
aluminum-complex soap grease,  
temperature range -45 °C to +120 °C,  
approval according to USDA H1

**lubrication fitting:**  
DIN 3425 D1/A (sizes 1/4 and 3/8)  
DIN 71 412 H1 (sizes 1/2 and 1/1)

**bearing clearance:**  
10 - 30 µm radial

**tolerances:**  
see page 10



order number		measurements [inches]							
type	right hand thread, left hand thread	d <sub>1</sub>	d <sub>2</sub> class 2	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	b <sub>1</sub>	b <sub>2</sub>	
BRM1/2-00	-501	500	5000-20 UNF	574	1.311	624	.472		
measurements [inches]		weight	calculation- factors	rotational speed limit	basic load rating	stat.			
type	h	l	l <sub>3</sub>	α [°]	kg	Y	v <sub>90</sub>	C <sub>10</sub> [N]	C <sub>0</sub> [N]
BRM1/2	2.460	1.496	.846	7,5	0,109	1,74	1,82	1125	4850 1850

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952510286
Diametro interno	12.7 mm
Diametro esterno	33.3 mm
Spessore	15.85 mm
Tipo	SA
Peso	109 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE