

Teste a snodo SA BRM3-4-00-501-DURBAL - BRM3-4-00-501-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/sa/brm3-4-00-501-durbal>

BRM3/4-00-501



male thread:
long-term
lubrication,
low maintenance,
shields,
dimensions in inches

**DURBAL® heavy-duty rod ends
with integral self-aligning
ball bearing**

rod end housing:
forged steel, case-hardened bearing race,
superfinished, rolled thread, surface gal-
vanized, free of Cr-VI


inner ring:
ball bearing steel, hardened,
superfinished

lubrication:
aluminum-complex soap grease,
temperature range -45 °C to +120 °C,
approval according to USDA H1

lubrication fitting:
DIN 3425 D11A (sizes 1/4 and 3/8)
DIN 71 412 H1 (sizes 1/2 and 1/1)

bearing clearance:
10 - 30 µm radial

tolerances:
see page 10



order number		measurements [inches]							
type	right hand thread / left hand thread	d ₁	d ₂ class 2	d ₃	d ₄	d ₅	b ₁	b ₂	b ₃
BRM3/4-00	-501	.750	.7500-16 UNF	.956	1.968	.984	.708		

type	measurements [inches]				weight [kg]	calculation- factors Y	rotational speed limit n _{max} [min ⁻¹]	basic load rating d _{yn.} C [N]	rating stat. C ₀ [N]
	h	l	l ₃	α [°]					
BRM3/4	3.090	1.850	1.102	7,0	0,341	2,32	2,43	825	7750 3380

CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952510323
Diametro interno	19.05 mm
Diametro esterno	49.99 mm
Spessore	24.99 mm
Tipo	SA
Peso	341 g
Il filo	Filetto destro
Lubrificazione	con
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE