

## Teste a snodo SI

### BEF3-4-20-502-DURBAL - BEF3-4-20-502-DURBAL

<https://www.123cuscinetti.it/cuscinetti-supporti/teste-snodo/si/bef3-4-20-502-durbal>

#### BEF3/4-20-502



**rod end housing:**  
forged steel, tempered, surface galvanized, free of Cr-VI


**joint ball:**  
ball bearing steel, hardened and ground, surface superfinished and chromium plated

**race:**  
nylon / teflon / glass fibre compound

**tolerances:**  
see page 10

**DURBAL® heavy-duty rod ends with integral spherical plain bearing**

**female thread:**  
maintenance free, dimensions in inches



order number		measurements [inches]									
type	right hand thread	left hand thread	d <sub>1</sub>	d <sub>2</sub>	d <sub>3</sub>	Class 2	d <sub>5</sub>	d <sub>7</sub>	d <sub>8</sub>	b <sub>1</sub>	b <sub>3</sub>
BEF 3/4-20	-502		.750	1.000	.7500-16 UNF		1.750	1.126	1.249	.874	.688
		measurements [inches]									
type	h	l	l <sub>1</sub>	l <sub>2</sub>	l <sub>3</sub>	SW	α <sub>1</sub> [°]	α <sub>2</sub> [°]	weight [kg]	basic load rating C <sub>r</sub> [N]	stat. C <sub>10</sub> [N]
BEF 3/4	2.905	1.718	.311	.854	1.007		11,0	7,0	0,229	24870	66200

## CARATTERISTICHE DEL PRODOTTO

Marchio	DURBAL
N° Ean13	3663952510613
Diametro interno	19.05 mm
Diametro interno	3/4" inch
Diametro esterno	44.45 mm
Diametro esterno	1 3/4" inch
Spessore	22.2 mm
Spessore	0.874" inch
Tipo	SI
Peso	229 g
Il filo	Filetto sinistro
Lubrificazione	senza
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE