


Gusci a rullini FC-20-K-NADELLA - FC-20-K-NADELLA

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/fc-20-k-nadella>

Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page. Types FC, FC-K, FCS and FCL-K clutches have stainless steel springs inserted in molded cage to position rollers for lockup.



Shaft Ø mm	Designation	F _z mm	D mm	C mm	Torque Nm	Overrun limiting speed for rotating shaft min*	Suitable needle bush
20	FC-20-K	20	26	16	30.0	11000	HK2012

Shaft Ø mm	Gaging			Z Minimum outer diameter of steel housing for torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun plug mm		Max. mm	Min. mm	Max. mm	Min. mm	
20	25.976	19.970	20.007	38	20.000	19.991	25.989	25.976	0.016

CARATTERISTICHE DEL PRODOTTO

Marchio	NADELLA
N° Ean13	3663952529462
Diametro interno	20 mm
Diametro esterno	26 mm
Spessore	16 mm
Peso	16 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE