


## Gusci a rullini FC-30-NADELLA - FC-30-NADELLA

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-rullini/gusci-rullini/fc-30-nadella>

### Drawn cup roller clutches

Shaft raceway and housing bore diameters that are necessary for proper mounting and operation are listed on the opposite page. Types FC, FC-K, FCS and FCL-K clutches have stainless steel springs inserted in molded cage to position rollers for lockup.



NADELLA

Shaft Ø mm	Designation	F <sub>o</sub> mm	D mm	C mm	Torque Nm	Overrun limiting speed rating for rotating shaft min*	Suitable needle bush
30	FC-30	30	37	20	99.1	7300	HK3012

Shaft Ø mm	Gaging			Z Minimum outer diameter of steel housing for torque mm	S - Shaft raceway diameter		H - Housing bore		Weight kg
	Ring gage mm	Clutch locking plug mm	Clutch overrun plug mm		Max. mm	Min. mm	Max. mm	Min. mm	
30	36.972	29.967	30.007	51	30.000	29.991	36.988	36.972	0.042

## CARATTERISTICHE DEL PRODOTTO

Marchio	NADELLA
N° Ean13	3663952529493
Diametro interno	30 mm
Diametro esterno	37 mm
Spessore	20 mm
Peso	42 g
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE