


Cuscinetti a sfera fila unica 1635-SC-NICE - 1635-SC-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/fila-unica/1635-sc-nice>

1600 Series™ Precision Ground Radial Bearings (con'1) **NICE**



| SUFFIX | | | | | | PRINCIPLE DIMENSIONS | |
|----------------------------|-----------------------------|---|------------------------|------------------------------------|------------------------------------|---------------------------------------|---------------------------------------|
| BEARING | DOUBLE SEAL | SINGLE SEAL | DOUBLE SHIELD | SINGLE SHIELD | OPEN | BORE d (in) (mm) | O.D. D (in) (mm) |
| 1635™ | | SC | | | | +0.000 +0.000 -0.0005 -0.013 | +0.000 +0.000 -0.0005 -0.013 |
| | | | | | | 0.7500 19.050 | 1.7500 44.450 |
| BASIC LOAD RATINGS | | | WEIGHT | ABUTMENT AND FILLET DIMENSIONS | | | |
| WIDTH B (in) (mm) | DYNAMIC C (lb) (N) | STATIC C ₀ (lb) (N) | W ⁰ (kg) | d _a min (in) (mm) | D _a max (in) (mm) | r max (in) (mm) | |
| 0.5000 12.700 | 2593 11539 | 1025 4581 | 0.20 0.09 | 0.965 24.51 | 1.530 38.85 | 0.025 0.64 | |

Weights given are for greased and sealed versions

CARATTERISTICHE DEL PRODOTTO

| | |
|------------------|---------------|
| Marchio | NICE |
| N° Ean13 | 3663952557687 |
| Diametro interno | 19.05 mm |
| Diametro esterno | 44.45 mm |
| Spessore | 12.7 mm |
| Peso | 90 g |
| Imballaggio | 1 |

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE