







## Cuscinetti a sfera fila unica 3005-SC-NICE - 3005-SC-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/fila-unica/3005-sc-nice>

**3000 Series® Semi-Ground Radial Bearings** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE: SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING						<b>BORE</b> <b>d</b> (in) (mm)	<b>O.D.</b> <b>D</b> (in) (mm)
	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.0005 $\text{O}$ -0.013
3005™	SC					0.3125 7.938	0.9063 23.020

WIDTH <b>B</b> (in) (mm)	BASIC LOAD RATINGS		WEIGHT <b>W</b> (lbs) (kg)	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC <b>C</b> (lbs) (N)	STATIC <b>Co</b> (lbs) (N)		<b>d<sub>a</sub> min</b> (in) (mm)	<b>D<sub>a</sub> max</b> (in) (mm)	<b>r max</b> (in) (mm)
0.3125 7.938	350 1558	300 1335	0.04 0.02	0.503 12.76	0.778 19.76	0.012 0.30

$\text{O}$  Weights given are for greased and sealed versions  
 $\text{O}$  3038 and larger +0.0005/-0.005 (-0.001/-0.13)

### CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952558165
Diametro interno	7.938 mm
Diametro esterno	23.02 mm
Spessore	7.938 mm
Peso	20 g
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE