


Cuscinetti a sfera fila unica 3007-DC-NICE - 3007-DC-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/fila-unica/3007-dc-nice>

3000 Series® Semi-Ground Radial Bearings **NICE®**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- BY-LON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE: DOUBLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3007™	DC					+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.005 -0.015
						0.4375 11.113	0.9063 23.020

WIDTH B (in) (mm)	BASIC LOAD RATINGS		WEIGHT W (lb) (kg)	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)		da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.3125 7.938	300 1508	300 1355	0.03 0.01	0.517 13.13	0.778 19.76	0.015 0.38

Ⓢ Weights given are for greased and sealed versions
Ⓣ 3038 and larger +.0000/-0.005 (-.000/-0.15)

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952558257
Diametro interno	11.113 mm
Diametro esterno	23.02 mm
Spessore	7.938 mm
Peso	10 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE