

Cuscinetti a sfera fila unica 3023-DS-NICE - 3023-DS-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/fila-unica/3023-ds-nice>

3000 Series® Semi-Ground Radial Bearings (con't) **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE: SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3023™						+0.005 +0.13 -0.000 -0.000	+0.000 +0.00 -0.0005 -0.013
						0.6250 15.875	1.3750 34.925

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Ca (lb) (N)	W ^⓪ (lb) (kg)	d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)
0.4375 11.113	940 4183	860 3783	0.10 0.05	0.753 19.13	1.203 30.56	0.025 0.64

^⓪ Weights given are for greased and sealed versions
^⓪ 3023 and larger +0.0005/-0.005 (-0.002/-0.13)

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952558578
Diametro interno	15.875 mm
Diametro esterno	34.925 mm
Spessore	11.113 mm
Peso	50 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE