

## Cuscinetti a sfera fila unica 3030-NS-NICE - 3030-NS-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/fila-unica/3030-ns-nice>

**3000 Series® Semi-Ground Radial Bearings (con't)** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE

SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3030™					NS	+0.005 +0.13 -0.000 -0.00	+0.000 +0.00 -0.0005 ⓐ
						0.7500 19.050	1.5250 41.275

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)	W <sup>ⓐ</sup> (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.5000 12.700	1300 5795	1010 4485	0.16 0.07	0.965 24.51	1.446 36.73	0.025 0.64

<sup>ⓐ</sup> Weights given are for greased and sealed versions  
<sup>ⓑ</sup> 3030 and larger +0.0005/-0.005 (+0.001/-0.13)

### CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952558691
Diametro interno	19.05 mm
Diametro interno	3/4" inch
Diametro esterno	41.275 mm
Diametro esterno	1 5/8" inch
Spessore	12.7 mm
Spessore	1/2" inch
Peso	70 g
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE