


Cuscinetti a sfera fila unica 3033-SC-NICE - 3033-SC-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/fila-unica/3033-sc-nice>

3000 Series® Semi-Ground Radial Bearings (con't) **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLUX RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm) +0.005 +0.00 -0.005	O.D. D (in) (mm) +0.000 +0.00 -0.005
3033™		SC				0.8250 15.875	1.7000 44.450

WIDTH B (in) (mm) +0.005 +0.00 -0.005	BASIC LOAD RATINGS		WEIGHT W (lb) (kg)	ABUTMENT AND FILLET DIMENSIONS		
	DYNAMIC C (lb) (N)	STATIC Ca (lb) (N)		d _a min (in) (mm)	D _a max (in) (mm)	r max (in) (mm)
0.5000 12.700	1300 5785	1025 4561	0.22 0.10	0.845 21.46	1.530 38.86	0.025 0.64

Ⓢ Weights given are for greased and sealed versions
Ⓣ 3038 and larger +0.0005/-0.005 (+0.001/-0.125)

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952558738
Diametro interno	15.875 mm
Diametro esterno	44.45 mm
Spessore	12.7 mm
Peso	100 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE