

Cuscinetti a sfera fila unica
3035-SS-NICE - 3035-SS-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/fila-unica/3035-ss-nice>

3000 Series® Semi-Ground Radial Bearings (con't)

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT RING
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- NYLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3035™					SS	+0.005 +0.13 -0.000 -0.005	+0.000 +0.50 -0.013 -0.005
						0.7500 19.050	1.7500 44.450

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.5000 12.700	1300 5785	1025 4561	0.20 0.09	0.965 24.31	1.530 38.86	0.025 0.64

Ⓢ Weights given are for greased and sealed versions
Ⓢ 3035 and larger +0.000/-0.005 (+/-0.002/-0.125)

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952558783
Diametro interno	19.05 mm
Diametro esterno	44.45 mm
Spessore	12.7 mm
Peso	90 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE