

Cuscinetti a sfera fila unica
3040-DS-NICE - 3040-DS-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/fila-unica/3040-ds-nice>

3000 Series® Semi-Ground Radial Bearings (con't)

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT RING
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1000 SERIES® BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- NYLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX						PRINCIPLE DIMENSIONS	
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3040™			DS			+0.005 +0.13 -0.000 -0.005	+0.000 +0.50 -0.000 -0.013
						0.8750 22.225	2.0000 50.800

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Co (lb) (N)	W (lb) (kg)	da min (in) (mm)	Da max (in) (mm)	r max (in) (mm)
0.5625 14.288	1480 6588	1350 6008	0.29 0.13	1.113 28.27	1.760 44.70	0.035 0.89

ⓘ Weights given are for greased and sealed versions
Ⓢ 3038 and larger +0.0001/-0.0006 (+/-0.002/-0.015)

CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952558875
Diametro interno	22.225 mm
Diametro esterno	50.8 mm
Spessore	14.288 mm
Peso	130 g
Imballaggio	1

contatto@123cuscinetti.it

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE