


## Cuscinetti a sfera fila unica 3041-DS-NICE - 3041-DS-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/fila-unica/3041-ds-nice>

**3000 Series® Semi-Ground Radial Bearings (con't)** **NICE**

- PRECISION GROUND ON ALL CONTACT SURFACES EXCEPT BORE
- EASY TO USE INCH DIMENSIONS
- ECONOMICAL BEARING FOR LIGHTER LOADS THAN THE 1600 SERIES™ BEARINGS
- MAX SPEED RANGE - 2500 - 3000 RPM
- HARDENED BEARING STEEL
- INFLON RETAINER STANDARD
- GREASED, DOUBLE SEALED OR DOUBLE SHIELDED STANDARD
- AVAILABLE: SINGLE SEALED OR SINGLE SHIELDED, OPEN, AND WITH OR WITHOUT GREASE



SUFFIX					PRINCIPLE DIMENSIONS		
BEARING	DOUBLE SEAL	SINGLE SEAL	DOUBLE SHIELD	SINGLE SHIELD	OPEN	BORE d (in) (mm)	O.D. D (in) (mm)
3041™			DS			+0.005 +0.13 -0.000 -0.005	+0.000 +0.00 -0.0005
						1.0000 25.400	2.0000 50.800

BASIC LOAD RATINGS			WEIGHT	ABUTMENT AND FILLET DIMENSIONS		
WIDTH B (in) (mm)	DYNAMIC C (lb) (N)	STATIC Ca (lb) (N)	W <sup>⓪</sup> (lb) (kg)	d <sub>a</sub> min (in) (mm)	D <sub>a</sub> max (in) (mm)	r max (in) (mm)
0.9625 14.288	1480 6598	1350 6008	0.28 0.12	1.187 30.40	1.760 44.70	0.035 0.89

<sup>⓪</sup> Weights given are for greased and sealed versions  
<sup>⓪</sup> 3038 and larger +.0000/-0.0005 (+.000/-0.13)

### CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952558929
Diametro interno	25.4 mm
Diametro esterno	50.8 mm
Spessore	14.288 mm
Peso	120 g
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE