


## Cuscinetti a sfera fila unica 400-26V-NICE - 400-26V-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/fila-unica/400-26v-nice>

**400** Series® Single Row Unground Radial Bearings **NICE**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm) +0.000/-0.0005	B O.D. (in) (mm) +0.0004/0.000	C WIDTH (in) (mm) +0.010/-0.010	D WIDTH (in) (mm) Reference	No.	Size (mm)
400™	26V	0.500 12.287	1.281 32.54	0.312 7.92	0.312 7.92	18	5/32 3.97

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
0.09 0.04	275 1224	193 859	133 592	107 478	75 334	52 231

Notes  
Balls - Carbon Steel Grade 200      Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened      Bearings supplied prelubricated with grease

### CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952560090
Diametro interno	12.7 mm
Diametro esterno	32.54 mm
Spessore	7.92 mm
Peso	40 g
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE