

## Cuscinetti a sfera fila unica 412-35V-NICE - 412-35V-NICE

<https://www.123cuscinetti.it/cuscinetti-supporti/cuscinetti-sfera/fila-unica/412-35v-nice>

**400 Series® Single Row Unground Radial Bearings** **NICE®**

- RADIAL UNGROUND BEARING
- EASY TO USE INCH DIMENSIONS
- MODERATE LOADS
- MAX SPEED RANGE - 1000 - 1200 RPM
- HARDENED RINGS
- FULL COMPLIMENT OF BALLS
- FULLY UNITIZED ASSEMBLY
- BEARING SUPPLIED PRE-GREASED STANDARD



BEARING	SUFFIX	BEARING DIMENSIONAL DATA				BALLS	
		A BORE (in) (mm) +0.000/-0.000	B O.D. (in) (mm) +0.0004/0.000	C WIDTH (in) (mm) +0.010/-0.010	D WIDTH (in) (mm) Reference	No.	Size
412™	35V	0.750 19.27	1.625 41.28	0.375 9.53	0.375 9.53	18	3/16 4.76

WEIGHT W (lbs) (kg)	RADIAL CAPACITY					
	REVOLUTIONS PER MINUTE					
	50	100	200	300	600	1200
	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)	(lbs) (N)
0.14 0.06	460 203	313 1393	216 961	174 774	121 538	85 378

Notes  
Balls - Carbon Steel Grade 200      Bands - 1010 Carbon Steel, Soft  
Rings - Carbon Steel, Case Hardened      Bearings supplied prelubricated with grease

### CARATTERISTICHE DEL PRODOTTO

Marchio	NICE
N° Ean13	3663952560144
Diametro interno	19.05 mm
Diametro esterno	41.28 mm
Spessore	9.53 mm
Peso	60 g
Imballaggio	1

[contatto@123cuscinetti.it](mailto:contatto@123cuscinetti.it)

+33 3 59 36 04 90

CRT4 de Lesquin 60 Rue Du Haut De Sainghin 59273 Fretin FRANCE